

IN AN EFFORT TO PROVIDE YOU WITH AN ACCURATE AND TIMELY QUOTE, PLEASE COMPLETE THE FORM BELOW:

Company Name: _____ Date: _____
 Contact Person: _____ Project Name: _____
 Address: _____
 City: _____ State: _____ Zip: _____ Architect: _____
 Phone: _____ Fax: _____ City/State: _____
 Email: _____ Date Product Required: _____

Fire Rated Glazing: (Please attach any additional information)

SuperLite I
Clear specialty tempered.
CPSC Cat. II impact safety rated.

20 min Use Starphire
 30 min by PPG

SuperLite I-W
Safety wired glass.
CPSC Cat. II impact safety rated.

20 min Misco (Diamond)
 45 min **OR**
 60 min Baroque (Square)
 90 min

SuperLite I-XL
Directional heat reflective
specialty tempered.
CPSC Cat. II impact safety rated.

20 min
 45 min
 60 min

SuperLite I-XL IGU
Bi-directional, heat reflective
specialty tempered.
CPSC Cat. II impact safety rated.

20 min
 45 min
 60 min

SuperLite X-45/60/90
Non-wired clear glazing for all
doors up to 100 sq. in. lite.
CPSC Cat. I & II impact safety rated.

45 min
 60 min
 90 min

Pyran® Platinum
Premium non-safety ceramics.

20 min 60 min
 45 min 90 min

Pyran® Platinum F
Premium filmed safety ceramics.
CPSC Cat. II impact safety rated.

20 min 90 min
 45 min 180 min
 60 min

Pyran® Platinum L
Premium laminated safety ceramics.
CPSC Cat. II impact safety rated.

20 min 90 min
 45 min 180 min
 60 min

SuperLite II-XL
Fire resistive transparent wall glazing.
Meets ASTM E-119.
CPSC Cat. II impact safety rated.

45 min Use Starphire
 60 min by PPG
 90 min
 120 min

SuperSecure II-XLS
Fire resistive transparent wall glazing
for forced entry requirements.
Meets ASTM E-119.
CPSC Cat. II impact safety rated.

45 min 90 min
 60 min 120 min

Int./Ext.	Qty.	Width	Height	Additional Comments

Fire Rated Framing: PLEASE FAX OR EMAIL SPECIFICATIONS AND DRAWINGS:

GPX ARCHITECTURAL SERIES 20-120 min aluminum clad fire protective and resistive

GPX BUILDERS SERIES FIRE PROTECTIVE 20-45 min fire protective

GPX BUILDERS SERIES TEMPERATURE RISE 60-90 min fire resistive

GPX CURTAIN WALL SYSTEM 60-120 min aluminum clad fire resistive

GPX HURRICANE SYSTEM 20-120 min aluminum clad fire resistive

GPX HURRICANE SYSTEM FLORIDA PRODUCT APPROVAL 20-120 min aluminum clad fire resistive

GPX BALLISTIC SYSTEM 20-120 min aluminum clad fire resistive