




60-120 Minute Fire Resistive Butt-Glazed Walls Comparison

All products meet ASTM E-119 with hose stream and CPSC impact safety requirements.

60 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Butt-Joint Sightline	Warranty	Thickness/ Weight per sq. ft.
SuperLite II-XLB 60 by SAFTI FIRST	USA	Clear	\$\$\$	7,980 	1-1/8 in butt-joint	5 years	2-1/2" / 21 lbs.
SuperLite II-XLM 60 by SAFTI FIRST	Imported	Clear	\$\$\$\$	3,855	5 mm clear butt-joint	5 years	1" / 12.3 lbs.
Clearview 60 System by Pilkington	Imported	Clear	\$\$\$\$	7,442	5 mm clear butt-joint	5 years	1" / 12.5 lbs.
Contraflam Structure 60 by Vetrotech	Imported	Clear	\$\$\$\$	7,574	1-1/8 in butt-joint	5 years	1-1/4" / 14 lbs.

120 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Butt-Joint Sightline	Warranty	Thickness/
SuperLite II-XLB 120 by SAFTI FIRST	USA	Clear	\$\$\$	7,980 	1-1/8 in butt-joint	5 years	2-1/2" / 21 lbs.
SuperLite II-XLM 120 by SAFTI FIRST	Imported	Clear	\$\$\$\$	4,256	5 mm clear butt-joint 	5 years	2-1/8" / 25 lbs.
Contraflam Structure 120 by Vetrotech	Imported	Clear	\$\$\$\$	4,536	1-1/8 in butt-joint	5 years	2-1/16" / 22.5 lbs.

This data is taken from the manufacturer/distributor's published information.
Please check with the individual manufacturer/distributor for the most up-to-date information.