

### PRODUCT ADVANTAGES



- ▶ Provides wall-to-wall and floor-to-ceiling transparency for up to 2 hours when combined with SuperLite II-XL glazing.
- ▶ Durable and structurally sound fire resistive aluminum clad framing system.
- ▶ Provides the clean appearance of conventional aluminum framing with uniform sightlines.
- ▶ Available in standard and custom finishes including high performance fluoropolymer finishes by PPG, clear anodized, bronze anodized, black anodized, Decoral®, any species of wood veneer, ornamental metal, and more.
- ▶ Can be used in both interior and exterior walls, openings, and temperature rise full-lite door applications.
- ▶ Can be customized to protect against hurricane, bullet, and blast.
- ▶ 5 year manufacturer's warranty.
- ▶ USA manufactured for fast lead times and competitive pricing.

#### FRAMING: with SuperLite II-XL glazing

Fire Rating	Max. CV Area	Max. CV Width	Max. CV Height
45-60 minutes	4,952 in. <sup>2</sup> (3.19 m <sup>2</sup> )	124 in. (3.15 m)	124 in. (3.15 m)
90-120 minutes	4,876 in. <sup>2</sup> (3.15 m <sup>2</sup> )	124 in. (3.15 m)	124 in. (3.15 m)

#### DOORS: with SuperLite II-XL glazing

Fire Rating	Max. Door Opening (Single Door)	Max. Door Opening (Pair Door)
60-90 minutes	48 in. x 108 in. (1.22 m x 2.74 m)	96 in. x 108 in. (2.44 m x 2.74 m)

### UL AND INTERTEK/WHI TESTED AND CERTIFIED



GPX Framing is listed and labeled by Intertek/Warnock-Hersey Inc. and Underwriters Laboratories, nationally recognized testing laboratories approved by OSHA.

### APPROVALS

UL 9, UL 10B, UL 10C, UL 263, UL 752-2005, NFPA 80, NFPA 251, NFPA 252, NFPA 257, ASTM E119, ASTM E152, ASTM E163, ASTM E2074, ASTM E2010-01, CPSC 16 CFR 1201 Cat. II, ULC CAN4-S101, ULC CAN4-S104, ULC CAN4-S106, NFRC 100, NFRC 200, NFRC 500.

### FIRE RESISTIVE

Contains smoke and flames, and blocks the passage of radiant heat.



### SPECIFICATIONS

**Profile Width:** 3 in. (76 mm) standard  
2-1/2 in. (64 mm) available

**Weight:** 12 lb./lineal foot (17.85 kg/m) standard

**Fire Rating:** 45-120 minutes with hose stream  
Meets ASTM E119, NFPA 251, and UL 263

**Ballistic Resistance:** Can be customized to meet up to Level 8, per UL 752-2005

#### NFRC Certifications:

0.34 SHGC with SuperLite II-XL 45 insulated with Solarban 60

0.31 SHGC with SuperLite II-XL 60 insulated with Solarban 60

0.27 SHGC with SuperLite II-XL 90 or 120 insulated with Solarban 60

0.40 U-Factor with SuperLite II-XL 45 insulated with Solarban 60

0.39 U-Factor with SuperLite II-XL 60 insulated with Solarban 60

0.34 U-Factor with SuperLite II-XL 90 or 120 insulated with Solarban 60

56 Condensation Resistance with SuperLite II-XL 45 insulated with Solarban 60

57 Condensation Resistance with SuperLite II-XL 60 insulated with Solarban 60

55 Condensation Resistance with SuperLite II-XL 90 or 120 insulated with Solarban 60

#### 3-Part Specifications:

Available at

[www.safti.com/specifications](http://www.safti.com/specifications)



Made in the USA




This two hour wall is an example of how GPX Framing with SuperLite II-XL 120 glazing enhances interior spaces with elegant transparency and natural daylight during everyday use, and protects building occupants from the potentially devastating effects of radiant heat by ensuring safe egress during a fire.


Project: David Eccles School of Business at the University of Utah in Salt Lake City, UT  
 Architect: MHTN Architects  
 Contract glazier: Mollerup Glass  
 Products used: SuperLite II-XL 120 (wall) and 90 (door) in GPX Framing

### TYPICAL DETAILS *More details available at [www.safti.com/details](http://www.safti.com/details)*

**SuperLite II-XL 120 in GPX Framing and  
SuperLite II-XL 90 in HMTR Door**



**SuperLite II-XL 120 in GPX Framing and  
SuperLite II-XL 90 in GPX Door**



The information provided herein is for reference only and is subject to change without notice. Please visit [www.safti.com](http://www.safti.com) for the most updated information.

© SAFTI FIRST June 2014