

## PRODUCT ADVANTAGES



- ▶ Most economical fire and safety rated glazing meeting all the standards for 90 minute temperature rise doors.
- ▶ Non-wired clear glazing providing the highest visual clarity.
- ▶ Impact safety rated to meet federal and code standards.
- ▶ Vision lite kits available in these sizes: 5"x35", 6"x27", 7"x22", and 12"x12".
- ▶ Can be used for interior and exterior applications.
- ▶ Lifetime manufacturer's warranty.
- ▶ USA manufactured for fast delivery and competitive pricing.

Fire Rating	Application	Max. CV Width	Max. CV Width	Max. CV Width	Stops
90 minutes	Doors (T)	100 in. <sup>2</sup> (0.06 m <sup>2</sup> )	10 in. (0.25 m)	33 in. (0.84 m)	5/8 in. (16 mm)

## TESTED AND CERTIFIED TO UL 10B AND 10C



SuperLite X-90 vision kit in 90 minute temperature rise door

SuperLite X-90 is listed and labeled by Intertek/Warnock-Hersey Inc., a nationally recognized testing laboratory approved by OSHA.



## FIRE PROTECTIVE

**Contains smoke and flames.  
Does not block radiant heat.**



**For fire resistive glazing that blocks radiant heat see SuperLite II-XL.**

## SPECIFICATIONS

**Thickness:** 3/4 in. (19 mm)

**Weight:** 9.0 lbs./sq.ft. (44 kg/m<sup>2</sup>)

**Fire Rating:** 90 minutes with hose stream

**Sound Transmission Rating:**  
Approx. STC 38

**Solar Heat Gain Coefficient:**  
0.67 SHGC

**Impact Safety Rating:**  
CPSC 16 CFR 1201 Cat. I and II

**3-Part Specifications:**  
Available at  
[www.safti.com/specifications](http://www.safti.com/specifications)

## APPROVALS

UL 10B, UL 10C, NFPA 80,  
NFPA 252, ULC CAN4-S104,  
CPSC 16 CFR 1201 Cat. I & II.



**Made in the USA**

## TYPICAL DETAILS *More details available at [www.safti.com/details](http://www.safti.com/details)*

### SuperLite X-90 in HMTR Door and SuperLite II-XL 120 in GPX Framing Transoms

