

Company Namo:



Data:

Quotation Request Form

IN AN EFFORT TO PROVIDE YOU WITH AN ACCURATE AND TIMELY QUOTE, PLEASE COMPLETE THE FORM BELOW:

Dompany Name.			Date					
Contact Person:			Project Nai	Project Name:				
Address:								
City:	_ State:	_ Zip:	Architect: _					
Phone:	_ Fax:		City/State:					
Email:	ail:			Date Product Required:				
Fire Rated Glazing]: (Please atta	ach any additional i	information)					
SuperLite I Clear specialty tempered. CPSC Cat. II impact safety rated.	20 min 30 min	Use Starphire by PPG	Int./Ext.	Qty.	Width	Height	Additional Comment	
SuperLite I-W Safety wired glass. CPSC Cat. II impact safety rated Misco (Diamond) Baroque (Square)	20 min 45 min 60 min 90 min							
SuperLite I-XL Directional heat reflective specialty tempered. CPSC Cat. II impact safety rated.	20 min 45 min 60 min							
SuperLite I-XL IGU Bi-directional, heat reflective specialty tempered. CPSC Cat. II impact safety rated.	20 min 45 min 60 min							
Pyran® Platinum Premium non-safety ceramics.		60 min 90 min						
Pyran® Platinum F Premium filmed safety ceramics. CPSC Cat. II impact safety rated.		60 min 180 min						
Pyran® Platinum L Premium safety ceramics.		60 min 180 min						
CPSC Cat. II impact safety rated.								
SuperLite II-XL Fire resistive transparent wall glazing Meets ASTM E-119. CPSC Cat. Il impact safety rated.	45 min 90 min							
	g. 60 min 120 min Use Starphire by PPG							

Fire Rated Framing: PLEASE FAX OR EMAIL SPECIFICATIONS AND DRAWINGS:

- SAFTIfire GPX 45 to 120 minute fire resistive, temperature rise framing system. Meets ASTM E-119.
- **SAFTIfire HM** 20 to 45 minute fire protective, non-temperature rise hollow metal framing system.
- SAFTIfire HMTR 60 to 90 minute temperature rise hollow metal framing system.
- SAFTIfire CW 45 to 120 minute temperature rise framing system for multi-story spans of glass. Meets ASTM E-119.

PLEASE FAX THIS COMPLETED FORM TO 415.824.5900. THANK YOU! For questions, please call 888.653.3333 or visit www.safti.com.