

120 MINUTE FIRE RESISTIVE GLASS PRODUCTS COMPARISON IN WALLS, SIDELITES AND TRANSOMS

All products meet ASTM E-119/UL 263/CAN-ULC S101 with hose stream and CPSC impact safety requirements.

FIRE RESISTIVE TEMPERED UNITS

120 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Warranty	Thickness/ Weight per sq. ft.	Custom Options
★ BEST OPTION							
SuperLite II-XL 120 by SAFTI FIRST	USA	Clear	\$\$\$	4,876 sq. in.	5 years	1-3/4 in. / 16 lbs.	Starphire Ultra-Clear by Vitro, Insulated, Low-E, Decorative, Hurricane, Forced Entry, Ballistic, Blast, X-Ray, etc.
SuperLite II-XLB 120 by SAFTI FIRST	USA	Clear	\$\$\$	7,980 sq. in.	5 years	2-5/8 in. / 23.4 lbs.	Starphire Ultra-Clear by Vitro, Insulated, Low-E, Decorative, Hurricane, Forced Entry, Ballistic, Blast, X-Ray, etc.
Contraflam 120 by Vetrotech	USA	Clear	\$\$\$\$	4,435 sq. in.	5 years	1-9/16 in. / 15.8 lbs.	Insulated, Low-E, Hurricane, Ballistic

FIRE RESISTIVE ANNEALED MULTILAMINATE

120 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Warranty	Thickness/ Weight per sq. ft.	Custom Options
SuperLite II-XLM 120 by SAFTI FIRST	Imported	Clear	\$\$\$\$	4,256 sq. in.	5 years	2-1/8 in. / 25 lbs.	Insulated
Pyrostop 120 by Pilkington	Imported	Clear	\$\$\$\$	3,730 sq. in.	5 years	2-1/4 in. / 22.9 lbs.	Insulated, Low-E, Decorative, Ballistic, X-Ray