


## 120 Minute Fire Resistive Glass Products Comparison in Walls, Sidelites and Transoms

All products meet ASTM E-119 with hose stream and CPSC impact safety requirements.

### Fire Resistive Tempered

120 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Custom Options	Warranty	Thickness/ Weight per sq. ft.
<b>SuperLite II-XL 120 by SAFTI FIRST</b> 	USA	Clear	\$\$\$	4,876	Starphire Ultra-Clear by PPG, Insulated, Low-E, Decorative, Hurricane, Forced Entry, Ballistic, Blast, X-ray, etc.	5 years standard / 10 years optional.	1-1/2" / 12 lbs.

### Fire Resistive Tempered Multilaminate

120 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Custom Options	Warranty	Thickness/ Weight per sq. ft.
<b>Contraflam 120 by Vetrotech</b>	USA	Clear	\$\$\$\$	4,435	Insulated, Low-E, Hurricane, Ballistic	5 years	1-9/16" / 15.8 lbs.

### Fire Resistive Annealed Multilaminate

120 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Custom Options	Warranty	Thickness/ Weight per sq. ft.
<b>SuperLite II-XLM 120 by SAFTI FIRST</b>	Imported	Clear	\$\$\$\$	4,256	Insulated	5 years	2-1/8" / 25 lbs.
<b>Pyrostop 120 by Pilkington</b>	Imported	Clear	\$\$\$\$	3,730	Insulated, Low-E, Decorative, Ballistic, X-ray	5 years	2-1/4" / 22.9 lbs.

This data is taken from the manufacturer/distributor's published information. Please check with the individual manufacturer/distributor for the most up-to-date information.