20 MINUTE FIRE PROTECTIVE GLASS PRODUCTS COMPARISON

All products meet CPSC impact safety requirements.

SPECIALTY TEMPERED

ı	20 Minute Product	Origin	Appearance	Cost	Hose Stream	Max. Area (sq. in.) in Doors	Warranty	Thickness/ Weight per sq. ft.
	★ BEST OPTION							
	SuperLite I by SAFTI FIRST	USA	Clear	\$	No*	3,436 sq. in. for AD** 3,341 sq. in. for SD** 3,299 sq. in. for WD**	Lifetime	1/4 in. / 3 lbs.
	Fireglass 20 by TGP	USA	Clear	\$	No*	3,204 sq. in.	Unknown	1/4 in. / 3 lbs.
	Pyroswiss by Vetrotech	USA	Clear	\$	No*	3,419 sq. in.	Unknown	1/4 in. / 3 lbs.

FILMED CERAMIC

20 Minute Product	Origin	Appearance	Cost	Hose Stream	Max. Area (sq. in.) in Doors	Warranty	Thickness/ Weight per sq. ft.
FireLite NT by TGP	Imported	Tinted	\$\$\$	Yes	3,204 sq. in.	3 years	3/16 in. / 2.5 lbs.
Keralite F/Keralite Select F by Vetrotech	Imported	Tinted	\$\$\$	Yes	3,627 sq. in.	3 years	3/16 in. / 2.5 lbs.

LAMINATED CERAMIC

20 Minute Product	Origin	Appearance	Cost	Hose Stream	Max. Area (sq. in.) in Doors	Warranty	Thickness/ Weight per sq. ft.
FireLite Plus by TGP	Imported	Tinted	\$\$\$\$	Yes	3,204 sq. in.	5 years	5/16 in. / 4 lbs.
Keralite L/Keralite Select L by Vetrotech	Imported	Tinted	\$\$\$\$	Yes	3,627 sq. in.	5 years	5/16 in. / 4 lbs.

^{*}Per the IBC, the hose stream test is not required for 20 minute doors.



^{**}AD = Aluminum Door / SD = Steel Door / WD = Wood Door