

90 MINUTE FIRE RESISTIVE GLASS PRODUCTS COMPARISON IN TEMPERATURE RISE DOORS

All products meet ASTM E-119/UL 263/CAN-ULC S101 with hose stream and CPSC impact safety requirements.

FIRE RESISTIVE TEMPERED UNITS

90 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Warranty	Thickness/ Weight per sq. ft.	Custom Options
★ <i>BEST OPTION</i>							
SuperLite II-XL 90 by SAFTI <i>FIRST</i>	USA	Clear	\$\$\$	4,876 sq. in.	5 years standard/ 10 years optional	1-1/2 in. / 14 lbs.	Starphire Ultra-Clear by Vitro, Insulated, Low-E, Decorative, Hurricane, Forced Entry, Ballistic, Blast, X-Ray, etc.
Contraflam 90 by Vetrotech	USA	Clear	\$\$\$\$	3,174 sq. in.	5 years	1-1/2 in. / 14.6 lbs.	Insulated, Low-E, Hurricane, Ballistic

FIRE RESISTIVE ANNEALED MULTILAMINATE

90 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Warranty	Thickness/ Weight per sq. ft.	Custom Options
SuperLite II-XLM 90 by SAFTI <i>FIRST</i>	Imported	Clear	\$\$\$\$	2,916 sq. in.	5 years	1-3/8 in. / 14.2 lbs.	Insulated
Pyrostop 90 by Pilkington	Imported	Clear	\$\$\$\$	3,724 sq. in.	5 years	1-7/16 in. / 17.6 lbs.	Insulated, Low-E, Decorative, Ballistic, X-Ray