SAFTIFIRST™
FIRE RATED GLAZING SOLUTIONS

Quick Quote

Quotation Request Form

IN AN EFFORT TO PROVIDE YOU WITH AN ACCURATE AND TIMELY QUOTE, PLEASE COMPLETE THE FORM BELOW:

Company Name: _____ Date: _____

Contact Person: _____ Project Name: _____

Address: _____

City: _____ State: _____ Zip: _____ Architect: _____

Phone: _____ Fax: _____ City/State: _____

Email: _____ Date Product Required: _____

Fire Rated Glazing: (Please attach any additional information)

SuperLite I
Clear specialty tempered.
CPSC Cat. II impact safety rated.
☐ 20 min ☐ 30 min ☐ Use Starphire by PPG

SuperLite I-W
Safety wired glass.
CPSC Cat. II
impact safety rated.
☐ 20 min ☐ 45 min ☐ 60 min ☐ 90 min ☐ Misco (Diamond) OR ☐ Baroque (Square)

SuperLite I-XL
Directional heat reflective
specialty tempered.
CPSC Cat. II impact safety rated.
☐ 20 min ☐ 45 min ☐ 60 min

SuperLite I-XL IGU
Bi-directional, heat reflective
specialty tempered.
CPSC Cat. II impact safety rated.
☐ 20 min ☐ 45 min ☐ 60 min

SuperLite X-45/60/90
Non-wired clear glazing for all
doors up to 100 sq. in. lite.
CPSC Cat. I & II impact safety rated.
☐ 45 min ☐ 60 min ☐ 90 min

Pyran® Platinum
Premium non-safety ceramics.
☐ 20 min ☐ 45 min ☐ 60 min ☐ 90 min

Pyran® Platinum F
Premium filmed safety ceramics.
CPSC Cat. II impact safety rated.
☐ 20 min ☐ 45 min ☐ 60 min ☐ 90 min ☐ 180 min

Pyran® Platinum L
Premium laminated safety ceramics.
CPSC Cat. II impact safety rated.
☐ 20 min ☐ 45 min ☐ 60 min ☐ 90 min ☐ 180 min

SuperLite II-XL
Fire resistive transparent wall glazing.
Meets ASTM E-119.
CPSC Cat. II impact safety rated.
☐ 45 min ☐ 60 min ☐ 90 min ☐ 120 min ☐ Use Starphire by PPG

SuperSecure II-XLS
Fire resistive transparent wall glazing
for forced entry requirements.
Meets ASTM E-119.
CPSC Cat. II impact safety rated.
☐ 45 min ☐ 60 min ☐ 90 min ☐ 120 min

Int./Ext.	Qty.	Width	Height	Additional Comments

Fire Rated Framing: PLEASE FAX OR EMAIL SPECIFICATIONS AND DRAWINGS:

GPX ARCHITECTURAL SERIES ☐ 20-120 min aluminum clad fire protective and resistive

GPX BUILDERS SERIES FIRE PROTECTIVE ☐ 20-45 min fire protective

GPX BUILDERS SERIES TEMPERATURE RISE ☐ 60-90 min fire resistive

GPX CURTAIN WALL SYSTEM ☐ 60-120 min aluminum clad fire resistive

GPX HURRICANE SYSTEM ☐ 20-120 min aluminum clad fire resistive

GPX HURRICANE SYSTEM FLORIDA PRODUCT APPROVAL ☐ 20-120 min aluminum clad fire resistive

GPX BALLISTIC SYSTEM ☐ 20-120 min aluminum clad fire resistive

PLEASE FAX THIS COMPLETED FORM TO 415.824.5900. THANK YOU! For questions, please call 888.653.3333 or visit www.safti.com.