

# 120 MINUTE FIRE RESISTIVE BUTT-GLAZED WALLS COMPARISON

All products meet ASTM E-119/UL 263/CAN-ULC S101 with hose stream and CPSC impact safety requirements.

120 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Warranty	Thickness/Weight per sq. ft.	Butt-Joint Sightline
<b>SuperLite II-XLB 120</b> by SAFTI <b>FIRST</b>	USA	Clear	\$\$\$	★ <b>LARGEST SIZE</b> 7,980 sq. in.	5 years	2-5/8 in. / 23.4 lbs.	1-1/8 in. butt-joint
<b>SuperLite II-XLM 120</b> by SAFTI <b>FIRST</b>	Imported	Clear	\$\$\$\$	4,256 sq. in.	5 years	2-1/8 in. / 25 lbs.	5 mm. clear butt-joint
<b>Contraflam Structure 120</b> by Vetrotech	Imported	Clear	\$\$\$\$	4,536 sq. in.	5 years	2-1/16 in. / 22.5 lbs.	1-1/8 in. butt-joint
<b>Clearview 120 System</b> by Pilkington	Imported	Clear	\$\$\$\$	7,442 sq. in.	5 years	1-13/16 in. / 21.9 lbs.	5 mm. clear butt-joint