


90 Minute Fire Resistive Glass Products Comparison in Temperature Rise Doors

All products meet ASTM E-119 with hose stream and CPSC impact safety requirements.

Fire Resistive Tempered

90 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Custom Options	Warranty	Thickness/ Weight per sq. ft.
SuperLite II-XL 90 by SAFTI FIRST 	USA	Clear	\$\$\$	4,876	Starphire Ultra-Clear by PPG, Insulated, Low-E, Decorative, Hurricane, Forced Entry, Ballistic, Blast, X-ray, etc.	5 years standard / 10 years optional.	1-1/2" / 12 lbs.

Fire Resistive Tempered Multilaminate

90 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Custom Options	Warranty	Thickness/ Weight per sq. ft.
Contraflam 90 by Vetrotech	USA	Clear	\$\$\$\$	3,174	Insulated, Low-E, Hurricane, Ballistic	5 years	1-1/2" / 14.6 lbs.

Fire Resistive Annealed Multilaminate

90 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Custom Options	Warranty	Thickness/ Weight per sq. ft.
SuperLite II-XLM 90 by SAFTI FIRST	Imported	Clear	\$\$\$\$	2,916	Insulated	5 years	1-3/8" / 14.15 lbs.
Pyrostop 90 by Pilkington	Imported	Clear	\$\$\$\$	3,724	Insulated, Low-E, Decorative, Ballistic, X-ray	5 years	1-7/16" / 17.6 lbs.

This data is taken from the manufacturer/distributor's published information. Please check with the individual manufacturer/distributor for the most up-to-date information.