

TGP 60-90 Minute Designer Series Doors Product Alert

For States in the 2012 and 2015 IBC

Includes AL, AK, AZ, AR, CA, CO, CT, DE, DC, FL, GA, ID, IN, IA, KY, LA, MD, MI, MN, MS, MO, MT, NE, NV, NJ, NM, NY, ND, OH, OK, OR, RI, SC, SD, TN, UT, VT, VA, WA, WV and WY as of June 2017



Before specifying **TGP's Designer Series 60-90 minute doors**, please read below as it may be in violation of the IBC - putting the project and building occupants at risk, as well as exposing the architect, owner and installer to liabilities.

◆ What does the 2012 and 2015 IBC require?

Section 716.5.5 highlights requirements for temperature rise doors in exit stairways and exit passageways, which are typically 60 and 90 minutes:

716.5.5 Doors in interior exit stairways and ramps and exit passageways. Fire door assemblies in interior exit stairways and ramps exit passageways shall have a maximum transmitted temperature rise of not more than 450° F (250° C) above ambient at the end of 30 minutes of standard fire test exposure.

Exception: The maximum transmitted temperature rise is not required in buildings equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.1 or 903.3.1.2.

716.5.5.1. Glazing in doors. Fire-protection-rated glazing in excess of 100 sq. in. (0.065 m²) is not permitted. Fire-resistance-rated glazing in excess of 100 sq. in. (0.065 m²) shall be permitted in fire door assemblies when tested as components of the door assemblies, and not as glass lights, and shall have a maximum transmitted temperature rise of 450° F (250° C) in accordance with Section 716.5.5.

◆ Can TGP's 90 minute Designer Series Door that exceeds 100 sq. inches in the vision area comply with this code?

No. According to the Designer Series Framing specification manual, the only glazing option for 90 minute Designer Series doors are FireLite NT and FireLite Plus, which do not meet ASTM E-119/UL 263. Therefore, it is limited to 100 sq. inches in the door vision area **regardless** if the building is fully sprinklered.

Even if Pyrostop 90 meets ASTM E-119/UL 263, it cannot be used in Designer Series Doors because it is too thick. **The Designer Series Door with FireLite NT/FireLite Plus that exceeds 100 sq. inches in the door vision area is NOT CODE-COMPLIANT.**

◆ Can TGP's 60 minute Designer Series Door that exceeds 100 sq. inches in the vision area comply with this code?

Not always. In order to meet code, **BOTH** conditions must be met: (1) the building must be equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.1 or 903.3.1.2 AND (2) the door must be glazed with Pyrostop 60. **The Designer Series Door with FireLite NT/FireLite Plus that exceeds 100 sq. inches in the door vision area is NOT CODE-COMPLIANT.**

What about the exception when the building is sprinklered - can it meet it then?

The exception in 716.5.5 only applies to the door material - not the glazing in the door. Even if the building is equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.1 or 903.3.1.2., the glass in the door vision area is still limited to 100 sq. inches. The only way to exceed 100 sq. inches in the door vision area is by using fire resistive glazing that meets ASTM E-119/UL 263.

In addition, the architect or building owner **must be certain** that the automatic sprinkler system installed throughout the building (and not just the area where the doors are located) meets the specific installation instructions in 903.3.1.1. or 903.3.1.2 **BEFORE** the temperature rise requirement for the door material can be waived. Simply having a building that is 'fully sprinklered' is not enough to evoke the exception.

If there is no confirmation that the building is equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.1 or 903.3.1.2, TGP's Designer Series Doors cannot be used at all. The Designer Series door is a hollow metal steel door, and there is no test or listing that shows that this door meets temperature rise requirements. The Designer Series Framing fact sheet also states that:

Note: This product is not intended for use in locations requiring a barrier to radiant heat, as it does not meet test standards ASTM E-119 or UL 263.

fireframes
DESIGNER SERIES DOORS & FRAMES

The fireframes[®] Designer Series Doors and Frames incorporate precise European engineering to provide a sleek, modern alternative to traditional door and frame styles. The unique design allows for a wide range of opening heights and widths, while maintaining excellent fire-rated performance and performance. Available in 60-90 minute fire ratings, this system can incorporate a wide range of the most glazing materials with glass can be up to 100 square inches.

FEATURES

- Easy installation due to light structural system
- Barrier to radiant heat
- Doors available in single leaf or double leaf design
- Full view frame
- Available with steel construction of door
- Barrier against heat conduction (see TGP's Designer Series Doors)
- Can be used with steel glass, Pyro-Guard[®], Pilkington Pyroshield[®] or the fire-rated heavy duty products
- Frame available in powder coated finish
- Frames supplied with or without hardware. Please check with TGP for compatibility
- Finish powder coating of the frame to match desired color scheme
- Manufactured in the U.S.
- Interchangeable

TESTS

• 60-90 minute fire rating available for the ratings in 60 minutes

TESTS

• The product is tested to meet the fire rating requirements of ASTM E-119 and UL 263. For product information, please contact your local distributor or TGP's Customer Service Department.

Compliance is required by the manufacturer to meet the minimum standards of code. The manufacturer (TGP) makes no claim that compliance with the minimum standards of code will ensure that the product will meet the minimum standards of code. Compliance with the minimum standards of code is the responsibility of the user. Compliance with the minimum standards of code is the responsibility of the user.

MODEL	MAX. GLAZING AREA (SQ. INCHES)	MAX. GLAZING HEIGHT (INCHES)	MAX. GLAZING WIDTH (INCHES)	MODEL	MAX. GLAZING AREA (SQ. INCHES)	MAX. GLAZING HEIGHT (INCHES)	MAX. GLAZING WIDTH (INCHES)
60 min.	100	60	60	90 min.	100	60	60
60 min.	100	60	60	90 min.	100	60	60
60 min.	100	60	60	90 min.	100	60	60
60 min.	100	60	60	90 min.	100	60	60

TGP | TECHNICAL GLASS PRODUCTS | fireframes | 600-524-5271

Who will be liable if non-compliant products are used?

It could be the architect, the building owner or the glazier – but it definitely won't be TGP. This much is clearly stated in the Designer Series specification manual:

2. BUILDING CODES

Due to the diversity in local, state / provincial, or federal laws and the codes that govern design and application of architectural products, it is the responsibility of the individual architect / owner and installer to ensure that products selected for use on projects comply with all the applicable building codes and laws. Technical Glass Products exercises no control over the use or application of its products, glazing materials, and operating hardware and assumes no responsibility thereof. Compliance of TGP project drawings with applicable codes for a given project shall be the responsibility of the Buyer.

Recommended Guidelines

- 1. REVIEW CONTRACT DOCUMENTS:** Review architectural drawings, specifications, and approved TGP project drawings, installation instructions, and shipping data to determine the scope of work for the project. The TGP project drawings are provided for reference and are not intended to be used as a substitute for the architect's drawings and specifications.
- 2. BUILDING CODES:** Due to the diversity in local, state / provincial, or federal laws and the codes that govern design and application of architectural products, it is the responsibility of the individual architect / owner and installer to ensure that products selected for use on projects comply with all the applicable building codes and laws. Technical Glass Products exercises no control over the use or application of its products, glazing materials, and operating hardware and assumes no responsibility thereof. Compliance of TGP project drawings with applicable codes for a given project shall be the responsibility of the Buyer.
- 3. COORDINATION WITH OTHER TRADES:** Coordinate with the general contractor or the responsible trades which impact installation (i.e., fireproofing, electrical, mechanical, plumbing, mechanical, etc.) in order to ensure that the installation will meet the requirements of the project.
- 4. INSTALLATION:** Installation must be in accordance with the manufacturer's instructions.
- 5. CHECK MEASUREMENTS:**
 - The manufacturer's drawings and specifications must be followed.
 - The manufacturer's drawings and specifications must be followed.
 - The manufacturer's drawings and specifications must be followed.

©2014 TGP | fireframes.com | Architectural Specification Manual | 11

Question for architects, glaziers and owners:
So why take the risk of specifying or purchasing a 60-90 minute door that doesn't always meet code?

Is the Designer Series Door available in aluminum?

No. This door is made of hollow metal steel frames, and only available in limited finishes. It cannot be anodized or clad with aluminum, and will not match the profiles or look of aluminum storefront.

The Designer Series Door is often packaged with TGP's Aluminum Series Framing. **Architects who are expecting an aluminum door when selecting the Aluminum Series Framing System (which currently does not include doors) should double-check which door is being supplied with it.**



How can I ensure that I am specifying or purchasing a 60-90 minute door product that will always meet code requirements?



To ensure that you are specifying or purchasing a 60-90 minute door product that **ALWAYS** meets code (regardless if the building is sprinklered), **SAFTI FIRST** has two code-compliant options that you can choose from:

GPX Builders Series Temperature Rise Doors with SuperLite II-XL 60 or 90 glazing – insulated steel door that meets the 450 degree F temperature rise criteria. Available in standard and custom finishes including high performance fluoropolymer finishes by PPG, stainless steel, and more. Offered with standard and custom hardware packages.

GPX Architectural Series Fire Resistive Doors with SuperLite II-XL 60 or 90 glazing – fire resistive aluminum door that meets the 250 degree F temperature rise criteria. Available in standard and custom finishes including clear anodized, bronze anodized, black anodized, high performance fluoropolymer finishes by PPG, ornamental metal, wood veneer, and more. Offered with standard and custom hardware packages.

View our [online project gallery](#) to see photos of our products installed in various code-approved applications throughout the country.

If you have any questions or would like assistance on any current or future projects, please don't hesitate to contact your [local SAFTI FIRST architectural representative](#) or call us toll-free at **888.653.3333**.