

IN AN EFFORT TO PROVIDE YOU WITH AN ACCURATE AND TIMELY QUOTE, PLEASE COMPLETE THE FORM BELOW:

Company Name: _____ Date: _____
Contact Person: _____ Project Name: _____
Address: _____
City: _____ State: _____ Zip: _____ Architect: _____
Phone: _____ Fax: _____ City/State: _____
Email: _____ Date Product Required: _____

Fire Rated Glazing: (Please attach any additional information)

SuperLite I Clear specialty tempered. CPSC Cat. II impact safety rated.	<input type="checkbox"/> 20 min <input type="checkbox"/> 30 min	<input type="checkbox"/> Use Starphire by PPG
SuperClear 45-HS Clear specialty glazing for all 45 min. applications. CPSC Cat. II impact safety rated.	<input type="checkbox"/> 45 min	
SuperClear 45-HS-LI Clear specialty low-iron glazing for all 45 min. applications. CPSC Cat. II impact safety rated.	<input type="checkbox"/> 45 min	
SuperLite I-XL Directional heat reflective specialty tempered. CPSC Cat. II impact safety rated.	<input type="checkbox"/> 20 min <input type="checkbox"/> 45 min	
SuperLite I-XL IGU Bi-directional, heat reflective specialty tempered. CPSC Cat. II impact safety rated.	<input type="checkbox"/> 20 min <input type="checkbox"/> 45 min	
SuperLite X-45/60/90 Non-wired clear glazing for all doors up to 100 sq. in. lite. CPSC Cat. I & II impact safety rated.	<input type="checkbox"/> 45 min <input type="checkbox"/> 60 min <input type="checkbox"/> 90 min	
Pyran® Platinum Premium non-safety ceramics.	<input type="checkbox"/> 20 min <input type="checkbox"/> 45 min	<input type="checkbox"/> 60 min <input type="checkbox"/> 90 min
Pyran® Platinum F Premium filmed safety ceramics. CPSC Cat. II impact safety rated.	<input type="checkbox"/> 20 min <input type="checkbox"/> 45 min <input type="checkbox"/> 60 min	<input type="checkbox"/> 90 min <input type="checkbox"/> 180 min
Pyran® Platinum L Premium laminated safety ceramics. CPSC Cat. II impact safety rated.	<input type="checkbox"/> 20 min <input type="checkbox"/> 45 min <input type="checkbox"/> 60 min	<input type="checkbox"/> 90 min <input type="checkbox"/> 180 min
SuperLite II-XL Fire resistive transparent wall glazing. Meets ASTM E-119. CPSC Cat. II impact safety rated.	<input type="checkbox"/> 45 min <input type="checkbox"/> 60 min <input type="checkbox"/> 90 min	<input type="checkbox"/> 120 min <input type="checkbox"/> Use Starphire by PPG
SuperLite II-XLM Fire resistive multilaminate glazing for butt-glazed applications. Meets ASTM E119. CPSC Cat. II impact safety rated.	<input type="checkbox"/> 60 min <input type="checkbox"/> 120 min	
SuperLite II-XLB Fire resistive tempered glazing for oversized and butt-glazed applications. Meets ASTM E119. CPSC Cat. II impact safety rated.	<input type="checkbox"/> 60 min <input type="checkbox"/> 120 min	<input type="checkbox"/> Use Starphire by PPG
SuperSecure II-XLS Fire resistive transparent wall glazing for forced entry requirements. Meets ASTM E-119. CPSC Cat. II impact safety rated.	<input type="checkbox"/> 45 min <input type="checkbox"/> 60 min	<input type="checkbox"/> 90 min <input type="checkbox"/> 120 min

Int./Ext.	Qty.	Width	Height	Application (Choose 1)	
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite <input type="checkbox"/> Transom	<input type="checkbox"/> Sidelite <input type="checkbox"/> Window

Fire Rated Framing: PLEASE FAX OR EMAIL SPECIFICATIONS AND DRAWINGS:

GPX Architectural Series	<input type="checkbox"/> 20-120 min aluminum clad fire protective & resistive
GPX Builders Series Fire Protective	<input type="checkbox"/> 20-45 min fire protective
GPX Builders Series Temperature Rise Doors	<input type="checkbox"/> 60-90 min temperature rise
GPX Curtain Wall System	<input type="checkbox"/> 60-120 min aluminum clad fire resistive

GPX Hurricane System	<input type="checkbox"/> 45-120 min aluminum clad fire resistive <input type="checkbox"/> with Florida Product Approval <input type="checkbox"/> with Texas Product Approval
GPX Blast System	<input type="checkbox"/> 45-120 min aluminum clad fire resistive
GPX Ballistic System	<input type="checkbox"/> 20-120 min aluminum clad fire resistive
GPX Firefloor System	<input type="checkbox"/> 60-120 min fire resistive floor system