

**IN AN EFFORT TO PROVIDE YOU WITH AN ACCURATE AND TIMELY QUOTE, PLEASE COMPLETE THE FORM BELOW:**

Company Name: \_\_\_\_\_ Date: \_\_\_\_\_  
 Contact Person: \_\_\_\_\_ Project Name: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_ Architect: \_\_\_\_\_  
 Phone: \_\_\_\_\_ Fax: \_\_\_\_\_ City/State: \_\_\_\_\_  
 Email: \_\_\_\_\_ Date Product Required: \_\_\_\_\_

**Fire Rated Glazing: (Please attach any additional information)**

**SuperLite I**  20 min  Use Starphire  
 Clear specialty tempered. CPSC Cat. II impact safety rated.  30 min by PPG

---

**SuperClear 45-HS**  45 min  
 Clear specialty glazing for all 45 min. applications. CPSC Cat. II impact safety rated.

---

**SuperClear 45-HS-LI**  45 min  
 Clear specialty low-iron glazing for all 45 min. applications. CPSC Cat. II impact safety rated.

---

**SuperLite I-XL**  20 min  45 min  
 Directional heat reflective specialty tempered. CPSC Cat. II impact safety rated.

---

**SuperLite I-XL IGU**  20 min  45 min  
 Bi-directional, heat reflective specialty tempered. CPSC Cat. II impact safety rated.

---

**SuperLite X-45/60/90**  45 min  60 min  90 min  
 Non-wired clear glazing for all doors up to 100 sq. in. lite. CPSC Cat. I & II impact safety rated.

---

**Pyran® Platinum**  20 min  60 min  45 min  90 min  
 Premium non-safety ceramics.

---

**Pyran® Platinum F**  20 min  90 min  45 min  180 min  60 min  
 Premium filmed safety ceramics. CPSC Cat. II impact safety rated.

---

**Pyran® Platinum L**  20 min  90 min  45 min  180 min  60 min  
 Premium laminated safety ceramics. CPSC Cat. II impact safety rated.

---

**SuperLite II-XL**  45 min  120 min  60 min  Use Starphire  
 Fire resistive transparent wall glazing. Meets ASTM E-119. CPSC Cat. II impact safety rated.  90 min by PPG

---

**SuperLite II-XLM**  60 min  120 min  
 Fire resistive multilaminate glazing for butt-glazed applications. Meets ASTM E119. CPSC Cat. II impact safety rated.

---

**SuperLite II-XLB**  60 min  Use Starphire  120 min by PPG  
 Fire resistive tempered glazing for oversized and butt-glazed applications. Meets ASTM E119. CPSC Cat. II impact safety rated.

---

**SuperSecure II-XLS**  45 min  90 min  60 min  120 min  
 Fire resistive transparent wall glazing for forced entry requirements. Meets ASTM E-119. CPSC Cat. II impact safety rated.

Int./Ext.	Qty.	Width	Height	Application (Choose 1)	
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window
				<input type="checkbox"/> Doorlite	<input type="checkbox"/> Sidelite
				<input type="checkbox"/> Transom	<input type="checkbox"/> Window

**Fire Rated Framing: PLEASE FAX OR EMAIL SPECIFICATIONS AND DRAWINGS:**

**GPX Architectural Series**  20-120 min aluminum clad fire protective & resistive

---

**GPX Builders Series Fire Protective**  20-45 min fire protective

---

**GPX Builders Series Temperature Rise Doors**  60-90 min temperature rise

---

**GPX Curtain Wall System**  60-120 min aluminum clad fire resistive

**GPX Hurricane System**  45-120 min aluminum clad fire resistive with Florida Product Approval  with Texas Product Approval

---

**GPX Blast System**  45-120 min aluminum clad fire resistive

---

**GPX Ballistic System**  20-120 min aluminum clad fire resistive

---

**GPX Firefloor System**  60-120 min fire resistive floor system