



 **SAFTI***FIRST*[™]

Fire Rated Glazing and Framing Solutions |



SuperLite™ Fire Rated Glass

Fire Resistive Glazing	Features	Applications
SuperLite™ II·XL 45 Fire Resistive Tempered Glazing	45 minute, CPSC Cat. II, ASTM E119 tested, clear transparent glazing that blocks radiant heat transfer. Can be customized to include energy performance, noise abatement benefits, bullet resistance, hurricane resistance, and unlimited decorative options.	Fire protective doors, sidelites, openings and transoms.  Now available with Starphire® Ultra Clear Glass by PPG.
SuperLite™ II·XLM 45 Fire Resistive Multilaminated Glazing	45 minute, CPSC Cat. II, ASTM E119 tested, clear fire resistive multilaminated glazing that blocks radiant heat transfer. Can be customized to include energy performance, security and unlimited decorative and custom glass options.	Fire protective doors, sidelites, openings and transoms.
SuperLite™ II·XL 60-120 Fire Resistive Tempered Glazing	60-120 minute, CPSC Cat. II, ASTM E119 tested, clear transparent glazing that blocks radiant heat transfer. Can be customized to include energy performance, noise abatement benefits, bullet resistance, hurricane resistance, and unlimited decorative options.	Fire resistive doors and wall assemblies.  Now available with Starphire® Ultra Clear Glass by PPG.
SuperLite™ II·XLM 60-120 Fire Resistive Multilaminated Glazing with Butt-Glazed Option	60-120 minute, CPSC Cat. II, ASTM E119 tested, clear fire resistive multilaminated glazing that blocks radiant heat transfer. Can be customized to include energy performance, security and unlimited decorative and custom glass options.	Fire resistive doors and wall assemblies. Available in butt-glazed applications.
SuperLite™ II·XLB Fire Resistive Tempered Glazing for Oversized and Butt-Glazed Applications	60-120 minute, CPSC Cat. II, ASTM E119 tested, clear transparent glazing that blocks radiant heat transfer. Can be customized to include energy performance, noise abatement benefits, bullet resistance, hurricane resistance and unlimited decorative options.	Fire resistive wall assemblies. Available in butt-glazed applications.  Now available with Starphire® Ultra Clear Glass by PPG.
SuperSecure™ II·XLS 45-120 Fire Resistive Security Glazing	45-120 minute, CPSC Cat. II, ASTM E119 tested, clear transparent wall glazing that blocks radiant heat transfer and meets forced entry requirements.	Fire resistive doors, openings and wall assemblies for prisons and other high security areas.
Fire Protective Glazing	Features	Applications
SuperLite™ I Fire Protective Specialty Tempered	20 minute, CPSC Cat. II, clear specialty tempered glazing. Decorative options also available.	Fire protective doors and partitions.  Now available with Starphire® Ultra Clear Glass by PPG.
SuperClear 45-HS <small>Patent Pending</small> Fire Protective Clear Specialty Glazing that meets Hose Stream	45 minute, CPSC Cat. II, clear specialty fire protective glazing that meets all requirements for 45 minute applications.	Fire protective doors, sidelites, openings and transoms.
SuperClear 45-HS-LI <small>Patent Pending</small> Fire Protective Low-iron Specialty Glazing that meets Hose Stream	45 minute, CPSC Cat. II, low-iron, specialty fire protective glazing that meets all requirements for 45 minute applications.	Fire protective doors, sidelites, openings and transoms.  Low-iron.
SuperLite™ I·XL & I·XL IGU Fire Protective Specialty Tempered with Partial Radiant Heat Protection	20-45 minute, CPSC Cat. II, directional or bi-directional IGU clear specialty tempered glazing with partial radiant heat protection.	Fire protective doors, sidelites, openings and transoms. SuperLite I-XL and SuperLite I-XL IGU do not meet ASTM E119 and requires AHJ approval for 45 minute applications. Please visit www.safti.com/AHJ for more information.
SuperLite™ I·W Fire Protective Wired with Safety Film	20-90 minute, CPSC Cat. II safety wired glazing.	Fire protective doors, sidelites, openings and transoms. 60-90 minute ratings are limited to 100 square inches in temperature rise doors, and up to the maximum size tested in non-temperature rise doors.
SuperLite™ X-45/60/90 <small>Patent Pending</small> Fire Protective Door Lites up to 100 square inches	45/60/90 minute clear, non-wired, and tint free glazing that meets all the fire and safety requirements for temperature rise doors.	45/60/90 minute door vision lites limited to 100 square inches.
PYRAN® Platinum Fire Protective Non-safety Ceramic	20-90 minute ceramic glass. No impact resistance.	Fire protective openings and transoms where human impact safety requirements do not apply.

SuperLite™ Fire Rated Glass

Fire Protective Glazing	Features	Applications
PYRAN® Platinum F <small>Fire Protective Filmed Safety Ceramic</small>	20-180 minute filmed ceramic glass. Impact safety rated to CPSC Cat. II.	Fire protective doors, sidelites and openings where impact is a concern. 60-180 minute ratings are limited to 100 square inches in temperature rise doors, and up to the maximum size tested in non-temperature rise doors.
PYRAN® Platinum L <small>Fire Protective Laminated Safety Ceramic</small>	20-180 minute laminated ceramic glass. Impact safety rated to CPSC Cat. II.	Fire protective doors, sidelites and openings where impact is a concern. 60-180 minute ratings are limited to 100 square inches in temperature rise doors, and up to the maximum size tested in non-temperature rise doors.

GPX GLASS PROTEX Fire Rated Framing

Framing System	Features	Applications
GPX ARCHITECTURAL SERIES	Fire protective and resistive, aluminum framing system available in multiple profiles. Offered in standard and custom finishes, including high performance fluoropolymer finishes by PPG, clear anodized, bronze anodized, Decoral®, any species of wood veneer, ornamental metal, and more.	Doors Openings Walls
GPX SNAPCAP SERIES	Patent-pending, easy to install, fire resistive system with slip-fit joinery and features extruded aluminum covers that mechanically snap to a tube steel core that provides structure and fire resistive endurance. Available in multiple finishes and profiles.	Openings Walls
GPX BUILDERS SERIES FIRE PROTECTIVE	Fire protective framing system available on multiple profiles. Offered in standard and custom finishes including high performance fluoropolymer finishes by PPG, stainless steel and aluminum clad.	Doors Openings
GPX BUILDERS SERIES TEMPERATURE RISE	Temperature rise door framing system available in multiple profiles. Offered in standard and custom finishes including high performance fluoropolymer finishes by PPG, stainless steel and aluminum clad.	Doors
GPX CURTAIN WALL SERIES	Fire resistive aluminum framing system available in multiple profiles for multi-story spans of glass.	Curtain Walls
GPX HURRICANE SERIES GPX HURRICANE SERIES FLORIDA PRODUCT APPROVAL	Fire resistive, hurricane rated, aluminum framing system. Offered in standard and custom finishes including high performance fluoropolymer finishes by PPG, clear anodized, bronze anodized, black anodized, Decoral®, any species of wood veneer, ornamental metal, and more.	Doors Openings Walls
GPX BALLISTIC SERIES	Fire resistive, ballistic rated aluminum framing system. Offered in standard and custom finishes including high performance fluoropolymer finishes by PPG, clear anodized, bronze anodized, black anodized, Decoral®, any species of wood veneer, ornamental metal, and more.	Doors Openings Walls
GPX BLAST SERIES	Fire resistive, blast rated, aluminum framing system. Offered in standard and custom finishes including high performance fluoropolymer finishes by PPG, clear anodized, bronze anodized, black anodized, Decoral®, any species of wood veneer, ornamental metal and more.	Openings Walls
GPX FIREFLOOR SYSTEM	Fire resistive glass floor assembly.	Floors

Choosing Fire Rated Glass

Fire Protective




- Contains smoke and flames.
- 20 to 45 minute ratings limited to applications that are less than 25% of the wall area.
- 60 to 180 minute ratings limited to 100 sq. in. for use in temperature rise doors.

Fire Protective - Heat Reflective



- Reflects dangerous radiant heat back towards the source.
- Provides partial radiant heat protection suitable for building exits and property lines.
- Does not meet ASTM E119 and requires AHJ approval for 45 and 60 minute applications. Please visit www.safti.com/AHJ for more information.

Fire Resistive



- Contains smoke, flames and blocks the passage of radiant heat.
- Limits the temperature rise on the non-fire side to 250°F above ambient even when the other side reaches temperatures over 1800°F.
- Does not have the size limitations that fire protective products do.
- Can be used wall-to-wall and floor-to-ceiling when installed with an equally rated framing system.

SAFTIFIRST Glass Products

SuperLite™ I
SuperClear 45-HS
SuperClear 45-HS-LI
SuperLite™ X-45/60/90
SuperLite™ I^W
 PYRAN® Platinum
 PYRAN® Platinum F
 PYRAN® Platinum L

SuperLite™ I^{XL}
SuperLite™ I^{XL}₁₆₀

SuperLite™ II^{XL}
SuperLite™ II^{XL}M
SuperLite™ II^{XL}B
SuperSecure™ II^{XLS}

Radiant Heat Transmission Through Fire Rated Glazing

