

### LIMITED WARRANTY

FURNISHED TO: SAMPLE

PROJECT: SAMPLE  
SALES  
ORDER:

SAFTI *FIRST* warrants that their products shall be free from defective material and comply with SAFTI *FIRST*'s published Quality Specifications and Inspection Standards for a period of five (5) years from the date of delivery provided that said products have been installed and maintained in accordance with SAFTI *FIRST*'s installation instructions and published maintenance recommendations. This warranty is limited to defects in the door, window or wall framing and glazing manufactured by SAFTI *FIRST*. This warranty does not cover "hardware supplied by others" or any other field installed items. Should there be a defect found in operating difficulty with any field installed component, the respective manufacturer or product warranty agreement that covers the component in question should be responsible and contacted.

This warranty is limited to the repair or replacement of defective material or entire product and shall be determined at the discretion of SAFTI *FIRST* as to what action to take.

SAFTI *FIRST* extends the SuperLite II-XLM, as manufactured by AGC Glass Europe, limited warranty to the immediate buyer and does not include associates or other groups. The conditions of this warranty for the SuperLite II-XLM glazing material are as follows:

The guarantee shall be null and void if the products are processed, packaged, stored, transported, installed, placed, used or maintained in a way that is not fully compliant with the recommendations of SuperLite II-XLM's Storage, Handling and Glazing Instructions.

Due to the composition and the natural properties of the intumescent interlayers used in the manufacture of SuperLite II-XLM, the product may develop some minor imperfections such as small bubbles and slight distortion, which do not affect the free vision through the unit nor its fire resistance and shall not be considered as defect.

As usually applied in the glass industry, the guarantee does not cover breakage. The guarantee also excludes any defect and any related damage that becomes apparent after the expiration of the guarantee period.

The guarantee shall apply only after SAFTI *FIRST* has had the opportunity to assess the existence of the defects and under the scope of the guarantee, SAFTI *FIRST* shall supply free of charge, the same place of delivery as that of the original supply, in the same quantity and size, the defective SuperLite II-XLM product. Any other costs or damages are HERBY EXCLUDED UNDER THE GUARANTEE.

The guarantee shall apply only to glasses handled, transported, stored and installed in accordance with normal procedures applied in the glass industry and in particular with SAFTI *FIRST*'s instructions (see SuperLite II-XLM Storage, Handling and Glazing Instructions) **In particular, the warranty shall not apply in one of the following cases:**

- The fire resistant construction element and its placement do not meet the current regulations or the requirements or recommendations of SAFTI *FIRST*.
- The glass has been damaged or modified by crumbling, cutting, sawing, edge working, application of films or anti-solar varnishes, deliberate or accidental mistreatment, in transport, storage or incorrect maintenance or contrary to SAFTI *FIRST*'s recommendations.
- The edge protection has been altered or removed.
- The edge of glazing has been in contact with water, liquid or aggressive materials
- Water (condensation or infiltration) has been allowed to stagnate in the frame
- The glass has been exposed to abnormal stresses or temperatures, e.g. storage in the vicinity of radiators or other heat sources.
- The glass has been exposed to temperature exceeding 50 °C or below -40°C;
- Internal grade glasses have been exposed to direct U.V. radiation.

**The warranty is subject to the following provisions:**

- A liability under this warranty is limited to free repair or replacement (at the manufacturer's discretion) of defective glass and/or frames and shall not extend to any other damages in connection with defective glass. Installation of the replacement glass into GPX framing is not covered under this warranty.
- Manufacturer's warranties on component parts of materials may differ from the terms specified herein and will supersede SAFTI *FIRST*'s standard warranty.
- The manufacturer's liability will also not apply in cases where defects are not reported within 30 days after they have become recognizable by the initial buyer or by the users of the building into which SuperLite II-XLM has been installed. Liability will therefore expire at the latest 30 days after the expiration of the warranty, also if the defect has not been recognizable before expiration of the 5-year warranty period. Any glass replaced or repaired under this warranty is limited by the original warranty period and shall not be extended beyond the original five years.
- Furthermore, the conditions for quality complaints according to the manufacturer's general conditions of sale for export shall apply.
- If SuperLite II-XLM is exported to a country other than where the initial delivery has been made, the warranty will only be valid if the manufacturer has accepted this exportation.
- Building and safety codes vary widely throughout the world. SAFTI *FIRST* does not control nor will it be responsible for the selection of product supplied by others, configurations, or the glazing materials used in the manufacture of its door, window or wall systems. SAFTI *FIRST* makes no other warranties or representation, either expressed or implied, concerning product fitness for a particular purpose. SAFTI *FIRST* will fabricate to dimensions shown on approved drawings but will not take responsibility for failure of submitting party(s) shop drawing dimensions against job site conditions. In no event will SAFTI *FIRST* be liable for direct, indirect, special or consequential damages including but not limited to loss of profit or use.
- SAFTI *FIRST* reserves the right to inspect or have returned all products alleged to be defective excluding shipping and handling costs.
- SAFTI *FIRST* makes no other warranty, expressed or implied, regarding its products.

SAMPLE

\_\_\_\_\_  
Name, Title

SAMPLE

\_\_\_\_\_  
Date

## SUPERLITE II-XLM STORAGE, HANDLING AND GLAZING INSTRUCTIONS

*Failure to comply with these procedures may result in a void warranty*

### **Storage and Handling Instructions**

Inspect shipment as soon as it is received. Check for any damages on the crate and the materials that may have occurred during shipping. If there are signs of damage, document and communicate it immediately to SAFTI *FIRST*.

On racks, SuperLite II-XLM must be stored slightly inclined (6 to 10 degrees from vertical) and fully supported.

A soft spacer must be placed between each glazing.

Do not pile more than 20 sheets per rack.

SuperLite II-XLM must be stored in dry and ventilated conditions, at temperature between -40 degrees Celsius and 50 degrees Celsius (122 degrees Fahrenheit), not exposed to solar radiation or UV light.

### **Glazing Instructions**

SuperLite II-XLM cannot be cut on site and the edge protection tape must not be removed or damaged.

Before installation, SuperLite II-XLM must be checked to ensure that it is not damaged, especially along the edges.

The fire resistant properties may be altered if SuperLite II-XLM has been chipped or otherwise damaged. In such cases, it must not be installed.

Follow additional instructions in the drawings or other documents provided by SAFTI *FIRST*.

Do not allow any contact of the glazing's edges with water.

Avoid all glass to metal contact.

Do not exercise any restraint on the glazing.

Do not install SuperLite II-XLM in locations where the glass temperature may might exceed 50 degrees Celsius (122 degrees Fahrenheit).

For exterior applications, or in case of direct solar radiation on the glazing, SuperLite II-XLM is available as an external grade (EG), with a UV filter. SuperLite II-XLM External Grade must be correctly oriented with its stamp readable from the UV opposed side.