

SuperLite® X-45/60/90

Patent Pending

45/60/90 Minute
Fire Protective Glazing

PRODUCT ADVANTAGES



- ▶ The clearest, most economical fire and safety rated glazing meeting all the code requirements. The IBC limits all fire protective glazing used as door lites in temperature rise doors to 100 square inches.
- ▶ Meets the required hose stream test.
- ▶ Meets CPSC impact safety standards without the need of films or laminates.
- ▶ Non-wired and tint-free clear glazing providing the highest visual clarity.
- ▶ USA manufactured for fast delivery and competitive pricing.
- ▶ Lifetime manufacturer's warranty.

| Fire Rating | Application | Max. CV Area | Max. CV Width | Max. CV Height | Stops |
|---------------|-------------|---|-----------------|-----------------|-----------------|
| 45-90 minutes | Doors (T) | 100 in. ² (0.06 m ²) | 10 in. (0.25 m) | 33 in. (0.84 m) | 5/8 in. (16 mm) |

TESTED AND CERTIFIED TO UL 10B AND 10C




SuperLite® X-45/60/90 is listed and labeled by Intertek and Underwriters Laboratories, nationally recognized testing laboratories approved by OSHA.



FIRE PROTECTIVE

Contains smoke and flames.
Does not block radiant heat.



For fire resistive glazing that blocks radiant heat see SuperLite® II-XL.

SPECIFICATIONS

Thickness: 3/4 in. (19 mm)

Weight: 9.0 lbs./sq.ft. (44 kg/m²)

Sound Transmission Rating:
STC 37/OITC 35 in 3/4 in. (19 mm) standard profile in standard hollow metal frames.

Fire Rating: 45/60/90 minutes with hose stream

Visible Light Transmittance: 83

Impact Safety Rating:
CPSC 16 CFR 1201 Cat. I and II.

APPROVALS

UL 10B, UL 10C, NFPA 80
NFPA 252, ULC CAN4-S104,
CPSC 16 CFR 1201 Cat. I & II.

3-Part Specifications:

Available at
www.safti.com/specifications



www.safti.com

SAFTIFIRST
SAFETY AND FIRE TECHNOLOGY INC.

888.653.3333

SuperLite® X-45/60/90


Patent Pending

45/60/90 Minute
Fire Protective Glazing

TYPICAL DETAILS

More details available at www.safti.com/details

SuperLite® X-45/60/90 in GPX® Builders Series Temperature Rise Door and SuperLite® II-XL 120 in GPX® Architectural Series Transoms



Details not to scale.

The information provided herein is for reference only and is subject to change without notice. Please visit www.safti.com for the most up to date information.

© SAFTI FIRST® March 2022