## SuperLite I by SAFTI FIRST

## Health Product Declaration v2.2 created via: HPDC Online Builder

## HPD UNIQUE IDENTIFIER: 28446

CLASSIFICATION: 08 88 13 Fire-Rated Glazing

PRODUCT DESCRIPTION: SuperLite I offers the most economical fire and safety rated glazing available. Featuring 20 minute fire rated glazing, SuperLite I provides superior optical clarity over ceramics, and meets the highest human impact safety requirements. SuperLite I can be used for interior and exterior applications, and is available in specialty architectural make-ups and decorative patterns. Manufactured in the USA and carrying a lifetime warranty, SuperLite I offers both fast delivery and competitive pricing.

# Section 1: Summary

## CONTENT INVENTORY

- Inventory Reporting Format © Nested Materials Method
- C Basic Method
- Threshold Disclosed Per
- Material
- C Product

- Threshold Level © 100 ppm © 1,000 ppm © Per GHS SDS © Other
- Residuals/Impurities Considered in 1 of 1 Materials
- Explanation(s) provided for Residuals/Impurities? • Yes O No

## **Nested Method / Material Threshold**

All Substances Above th	he Threshold Indicated Are:		
Characterized	○ Yes Ex/SC ⊙ Yes ○ No		
% weight and role provi	ded for all substances.		
Screened	○ Yes Ex/SC		
All substances screened using Priority Hazard Lists with results disclosed.			
Identified	○ Yes Ex/SC   Yes ○ No		
All substances disclosed and Identifier.	d by Name (Specific or Generic)		

## CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

GREENSCREEN SCORE | HAZARD TYPE

CLEAR TEMPERED GLASS [ SODA LIME BOROSILICATE GLASS LT-UNK ]

## VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen

Benchmark or List translator Score ... LT-UNK

### Nanomaterial ... No

### INVENTORY AND SCREENING NOTES:

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 2.2, and discloses hazards associated with all substances present at or above 100 parts per million (ppm) in the finished product, along with the role and percent weight.

**CERTIFICATIONS AND COMPLIANCE** See Section 3 for additional listings.

VOC emissions: Inherently non-emitting source per LEED®

### CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1 and Option 2

Third Pa	arty Verified?	
C Yes		
No		

PREPARER: Self-Prepared VERIFIER: VERIFICATION #: SCREENING DATE: 2022-05-04 PUBLISHED DATE: 2022-05-04 EXPIRY DATE: 2025-05-04 This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

CLEAR TEMPERED GLASS	%: 100.0000 - 100.0000		
MATERIAL THRESHOLD: 100 pp	m RESIDUALS AND IMPURITIES	CONSIDERED: Yes	MATERIAL TYPE: Glass
mpurities are known or expected	OTES: Residuals and Impurities were "Consi d to be present at or above the Content Inver n provided in supplier disclosures and as pre	ntory Threshold indicated t	hat have a GS score of BM-1, LT-1, LT
OTHER MATERIAL NOTES: Clear	r float glass specially tempered to meet a 20	minute fire rating.	ID: 65997-17-
SODA LIME BOROSILICATE G			ID: 65997-17-
SODA LIME BOROSILICATE G	LASS	HAZARD SCREENING D	
SODA LIME BOROSILICATE G	LASS D: Pharos Chemical and Materials Library	HAZARD SCREENING D	ATE: 2022-05-04 15:16:40

SUBSTANCE NOTES: Chemical analysis of typical clear float glass: 72.6% Silica (14808-60-7 | BM-1); 13.9% Sodium Oxide (1313-59-3 | BM-2); 8.4% Calcium Oxide (1305-78-8 | BM-2); 3.9% Magnesium Oxide (1309-48-4; BM-3dg); 1.1% Aluminum Oxide (1344-28-1 | BM-2); 0.6% Potassium Oxide (12136-45-7 | BM-2); Sulfur Trioxide (7446-11-9 | BM- 2); 0.11% Iron Oxide (1332-37-2 | LT-UNK). Float glass used in this product contains approximately 20% recycled glass in the form of cullet.

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	Inherently non-emitting source per LEED®			
CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: Merced, CA 95341	ISSUE DATE: 2022-03- EXPIRY DATE: 28	CERTIFIER OR LAB: N/A		
CERTIFICATE URL:				

CERTIFICATION AND COMPLIANCE NOTES: Glass is considered an inherently non-emitting source of VOCs as per LEED.

## 😑 Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

### **GPX FRAMING - UNFINISHED**

HPD URL: https://tinyurl.com/2p8h4new

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES: SuperLite I glazing is typically used in conjunction with GPX Framing or GPX Builder Series Doors, although other framing systems or doors can be used.

**GPX BUILDER SERIES DOOR - UNFINISHED** 

HPD URL: https://tinyurl.com/2p8zsrbc

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES: SuperLite I glazing is typically used in conjunction with GPX Builder Series Doors or with GPX Framing, although other door and framing systems can be used.

## Section 5: General Notes

SuperLite I is listed and labeled by Intertek/Warnock-Hersey Inc. and Underwriters Laboratories, and meets the following standards: UL 9, UL 10B, UL 10C, NFPA 80, NFPA 252, NFPA 257, ASTM E152, ASTM E163, ASTM E2074, ASTM E2010-01, CPSC 16 CFR 1201 Cat. II. Specifications:

-Thickness: 1/4" (6mm) Also available in 1/2" (12mm)

-Weight: 3.0 lbs./sq.ft.

-Fire Rating: 20 minutes without hose stream

-Sound Transmission Rating: STC 28 rating

-Solar Heat Gain Coefficient: 0.82 SHGC

-Impact Safety Rating: CPSC 16 CFR 1201 Cat. I and II

### MANUFACTURER INFORMATION

MANUFACTURER: SAFTI FIRST ADDRESS: 100 N Hill Drive Suite 12 Brisbane CA 94005, USA WEBSITE: http://safti.com/ CONTACT NAME: Diana San Diego TITLE: VP of Marketing PHONE: 888-653-3333 EMAIL: DianaS@safti.com

LT-1 List Translator 1 (Likely Benchmark-1)

to a LT-1 or LTP1 score.)

NoGS No GreenScreen.

LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the

information contained within the list did not result in a clear mapping

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

#### KEY

#### Hazard Types

AQU Aquatic toxicity CAN Cancer DEV Developmental toxicity END Endocrine activity EYE Eye irritation/corrosivity GEN Gene mutation GLO Global warming

LAN Land toxicity MAM Mammalian/systemic/organ toxicity MUL Multiple NEU Neurotoxicity NF Not found on Priority Hazard Lists OZO Ozone depletion PBT Persistent, bioaccumulative, and toxic PHY Physical hazard (flammable or reactive) REP Reproductive RES Respiratory sensitization SKI Skin sensitization/irritation/corrosivity UNK Unknown

### GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)
BM-3 Benchmark 3 (use but still opportunity for improvement)
BM-2 Benchmark 2 (use but search for safer substitutes)
BM-1 Benchmark 1 (avoid - chemical of high concern)
BM-U Benchmark Unspecified (due to insufficient data)
LT-P1 List Translator Possible 1 (Possible Benchmark-1)

#### **Recycled Types**

PreC Pre-consumer recycled content PostC Post-consumer recycled content UNK Inclusion of recycled content is unknown None Does not include recycled content

#### Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

#### **Inventory Methods:**

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology Third Party Verified Verification by independent certifier approved by HPDC Preparer Third party preparer, if not self-prepared by manufacturer Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.

#### SuperLite I hpdrepository.hpd-collaborative.org